#### WWW.DIGITALKHODRO.COM ENGINE

#### 021-62999292

-		ATOR CONTI			
		1			
	CON	TENTS			
PRECAUTION		ON-VEHICLE REPAI	R	<sup>1</sup> 3	
PRECAUTIONS Precaution for Supplemental F (SRS) "AIR BAG" and "SEAT SIONER"	Restraint System	Exploded View Removal and Installation	 	3 3	
				:	
	•• •	•• O-		1 B	
انه (مسئولیت محدود	• •• بتال خودرو ساما	<b></b>			
انه (مسئولیت محدود رکاران خودرو در ایران					
· · ·					
رکاران خودرو در ایران	ه دی <u>جی</u> تال تعمیر	اولین سامان			
رکاران خودرو در ایران		اولین سامان			
رکاران خودرو در ایران	ه دیجیتال تعمیر	اولین سامان			
رڪاران خودرو در ايران	ه ديجيتال تعمير	اولین سامان			
رڪاران خودرو در ايران	ه ديجيتال تعمير	اولین سامان			
رکاران خودرو در ایران	ه ديجيتال تعمير	اولین سامان			

1

WWW.DIGITALKHODRO.COM ACC-1

021-62 99 92 92

WWW.DIGITALKHODRO.COM

< PRECAUTION >

### PRECAUTION

#### PRECAUTIONS

## Precaution for Supplemental Restraint System (SRS) "AIR BAG" and "SEAT BELT PRE-TENSIONER"

INFOID:000000005022452

The Supplemental Restraint System such as "AIR BAG" and "SEAT BELT PRE-TENSIONER", used along with a front seat belt, helps to reduce the risk or severity of injury to the driver and front passenger for certain types of collision. This system includes seat belt switch inputs and dual stage front air bag modules. The SRS system uses the seat belt switches to determine the front air bag deployment, and may only deploy one front air bag, depending on the severity of a collision and whether the front occupants are belted or unbelted. Information necessary to service the system safely is included in the "SRS AIR BAG" and "SEAT BELT" of this Service Manual.

#### WARNING:

- To avoid rendering the SRS inoperative, which could increase the risk of personal injury or death in the event of a collision which would result in air bag inflation, all maintenance must be performed by an authorized NISSAN/INFINITI dealer.
- Improper maintenance, including incorrect removal and installation of the SRS, can lead to personal injury caused by unintentional activation of the system. For removal of Spiral Cable and Air Bag Module, see the "SRS AIR BAG".
- Do not use electrical test equipment on any circuit related to the SRS unless instructed to in this Service Manual. SRS wiring harnesses can be identified by yellow and/or orange harnesses or harness connectors.

#### PRECAUTIONS WHEN USING POWER TOOLS (AIR OR ELECTRIC) AND HAMMERS

#### WARNING:

- When working near the Air Bag Diagnosis Sensor Unit or other Air Bag System sensors with the ignition ON or engine running, DO NOT use air or electric power tools or strike near the sensor(s) with a hammer. Heavy vibration could activate the sensor(s) and deploy the air bag(s), possibly causing serious injury.
- When using air or electric power tools or hammers, always switch the ignition OFF, disconnect the battery, and wait at least 3 minutes before performing any service.

#### WWW.DIGITALKHODRO.COM ACC-2

#### 021-62 99 92 92

#### WWW.DIGITALKHODRO.COM ACCELERATOR CONTROL SYSTEM

#### ON-VEHICLE REPAIR > ON-VEHICLE REPAIR ACCELERATOR CONTROL SYSTEM

#### **Exploded View**

INFOID:000000004900732

021-62999292



#### INSPECTION AFTER INSTALLATION

 Check that the accelerator pedal moves smoothly within the whole operation range when it is fully depressed and released.

WWW.DIGITALKHODRO.COM ACC-3

#### 021-62 99 92 92

Α.

ACC

#### WWW.DIGITALKHODRO.COM ACCELERATOR CONTROL SYSTEM

#### < ON-VEHICLE REPAIR >

#### NOTE:

On A/T and CVT models, the accelerator pedal becomes stiffer and will "click" at 75 % stroke. This is not a malfunction.

Check accelerator pedal securely returns to the fully released position.

• For the electrical inspection of accelerator pedal position sensor. Refer to EC-221. "Description", EC-224. "Description", and EC-231. "Description".

# **حیجیتال خودرو** سامانه (مسئولیت محدود)



اولین سامانه دیجیتال تعمیرکاران خودرو در ایران

----

i ;

. .

•

.

WWW.DIGITALKHODRO.COM ACC-4

021-62999292